



conveyor products

BELT WIDTHS

Belle Banne H Type belt cleaner is suitable for all belt widths from 400 mm – 3000 mm.

REVERSING CONVEYORS

The Belle Banne H type belt cleaner can be used on reversing belts. Install one at either end, or one at the primary discharge end of your conveyor.

• HEAVY DUTY CONSTRUCTION

Belle Banne cleaner poles are the strongest around. All poles are schedule 80 material, ensuring they are fit for tough mining applications. Heavy Duty Cushions and Suspension arms are available on request for tough applications.

• STAINLESS STEEL

Belle Banne cleaners are available in either powder coated mild steel, or 304 stainless steel. 316 grade available on request.

CONTACT US

Mail: P0 Box 4395

Westfield Penrith NSW 2750

Address: Unit 2, 27 Jack Williams Drive

Penrith NSW 2750

Phone: +61 2 4724 9444 Fax: +61 2 4732 5881

Email: info@bellebannecp.com.au

ABN 12 137 362 497

www.bellebannecp.com.au

H Type Primary Belt Cleaner



The Belle Banne H type Belt cleaner has been the leader in belt cleaning technology for more than 30 years.

The original H type cleaner was developed by Belle Banne as a primary belt cleaner suitable for demanding applications.

Whether it is the only cleaner in use on a conveyor, or the first in a high performance cleaning system, the Belle Banne H type belt cleaner should be your first choice.

Available in all sizes to suit your belt width, and in a range of materials to optimise life and performance, the Belle Banne H Type belt cleaner provides multiple options to suit your cleaning needs.



SEGMENTED BLADES

The H type belt cleaner consists of individual 200 mm segmented blades, each one mounted on a rubber cushion. Seperate blades ensure constant blade to belt contact on uneven surfaces, guaranteeing maximum cleanliness.

LONG LASTING TUNGSTEN

Belle Banne has long been the leader in its class when it comes to tungsten. Our tungsten has a proven track record for consistent wear and long blade life. No other tungsten blade comes close.

OPTIMAL POSITION

The H type is positioned on the head, or discharge pulley, and sits out of the flow of regular material in the conveyor chute or transfer, ensuring the cleaner does not become bogged in material.

5 different suspension arm sizes are available to match your pulley diameter, and make certain that the cleaner is positioned correctly for optimum performance every time.





H Type Primary Belt Cleaner Ordering Information

Belt (mm)	Tip (mm)	Pole Lgth (mm)	Pole Diam (mm)	Arm Size (see table)	MILD STEEL		STAINLESS STEEL		
					Item Code	Ordering Number	Item Code	Ordering Number	Wgt (kgs)
450	400	1450	60	SS S M	110001 110002 110003	HBB450x400SS HBB450x400S HBB450x400M	115001 115002 115003	HBB450x400SS-304 HBB450x400S-304 HBB450x400M-304	32
750	600	1750	60	SS S M	110004 110005 110006	HBB750x600SS HBB750x600S HBB750x600M	115004 115005 115006	HBB750x600SS-304 HBB750x600S-304 HBB750x600M-304	39
900	800	1900	60	SS S M	110007 110008 110009	HBB900x800SS HBB900x800S HBB900x800M	115007 115008 115009	HBB900x800SS-304 HBB900x800S-304 HBB900x800M-304	44
1050	1000	2050	60	SS S M	110010 110011 110012	HBB1050x1000SS HBB1050x1000S HBB1050x1000M	115010 115011 115012	HBB1050x1000SS-304 HBB1050x1000S-304 HBB1050x1000M-304	48
1200	1200	2600	60	SS S M L	110013 110014 110015 110016	HBB1200x1200SS HBB1200x1200S HBB1200x1200M HBB1200x1200L	115013 115014 115015 115016	HBB1200x1200SS-304 HBB1200x1200S-304 HBB1200x1200M-304 HBB1200x1200L-304	52
1500	1400	2900	73	SS S M L	110017 110018 110019 110020	HBB1500x1400SS HBB1500x1400S HBB1500x1400M HBB1500x1400L	115017 115018 115019 115020	HBB1500x1400SS-304 HBB1500x1400S-304 HBB1500x1400M-304 HBB1500x1400L-304	66
1600	1600	3000	73	S M L	110021 110022 110023	HBB1600x1600S HBB1600x1600M HBB1600x1600L	115021 115022 115023	HBB1600x1600S-304 HBB1600x1600M-304 HBB1600x1600L-304	70
1800	1800	3200	73 Braced	S M L	110024 110025 110026	HBB1800x1800S HBB1800x1800M HBB1800x1800L	115024 115025 115025	HBB1800x1800S-304 HBB1800x1800M-304 HBB1800x1800L-304	97

WHERE IS IT USED?

- Coal
- Iron ore
- Hard rock
- Heavy metals
- Sand and gravel
- Recycling
- Steel mills
- Power gen

The Belle Banne H type can remove up to 85% of your carry back, or up to 97% when used with a secondary cleaner – ask us how.

SUSPENSION ARM SELECTION CHART

Pulley Dia + Belt +lagging (mm)	Arm Size
Up to 499 mm	SS
500 - 799	S
800 – 999	M
1000 – 1199	L
Over 1200	LL

"GREEN MEANS CLEAN"